

NNC experimental facilities for out-of-pile test conduction



Kazakhstan

17 September, 2004

Presented by Yu. Vassiliev

National Nuclear Center of the Republic of Kazakhstan

Principal Directions of NNC RK Activity

Radioecology of those Kazakhstan regions where nuclear tests were conducted and where atomic industry plants and nuclear facilities are located

Nuclear power engineering and its safety

Nuclear physics and radiation materials structure testing in the field of nuclear power

Application of nuclear-physical methods and scientific technologies in national economy of the Republic of Kazakhstan


Study of nuclear testing impact on the earth's crust and nuclear test monitoring

Nuclear Infrastructure Monitoring

Experiments on LWR safety validation in NNC RK

- **Experiments on fuel – coolant interaction (FCI)**
- **Experiments on molten core – concrete interaction (MCCI) with decay heat modeling in debris**
- **Experiments on research of corium interaction with reactor pressure vessel steel (LHI)**
- **Experiments on research of corium interaction with reactor pressure vessel steel with decay heat modeling in debris (IVR-AM)**


Electric melt furnace of LAVA-B facility



EMF OF LAVA-B FACILITY

MAJOR EMF PARAMETERS

Mass of molten burden with uranium dioxide, kg	up to 60
Melt temperature, K	3300
Technique for melting	Induction
Duration of warming and melting the burden, min	up to 60
Maximum active power supplied to EMF crucible, kW	up to 165



- 1 - position indicator; 2 - EMF bottom; 3 - shatter saddle;
 4 - drain bush; 5 - shatter valve; 6 - rod of the pneumocylinder;
 7 - collapsing armored protective board (graphitic fabric 2 layers + wire mesh); 8 - protective slat; 9 - knife (outlined position is marked new designed detail)


SHUTTER FOR EMF ("LAVA-B" FACILITY)

The parts of high temperature Electric melt furnace

INFRARED TEMPERATURE SENSOR



STAGE OF EMF ASSEMBLY AND PROCEDURES ON INSTALLATION OF SENSOR STRUCTURAL ELEMENTS IN THE EMF CRUCIBLE.



The pellets of UO_2



THE DRAWING OF EMF CRUCIBLE

ASSEMBLED CASSETTE



SENSOR MOUNTING ON THE EMF LID



THE VIEWS OF EMF CRUCIBLE


INSERTS FOR EMF CRUCIBLES



Tungsten insert



Tantalum insert



Tantalum insert



EMF crucibles

Equipment for small-scale experiments

High frequency induction heating VCG-135 stand



VCG-135 working chamber



Maximum heating temperature 3000 deg.C (at 0.5 MPa)

Small-scale experiments on Electric melting furnace material testing




NbC+TaC coating on graphite crucible



Tungsten insert + TaC coating on graphite crucible



Combined insert W+Ta



Modeling of melt discharging hole in the crucible bottom



Metallic zirconium coating usage



Heightened content of metallic zirconium in the initial burden




Graphite crucible coated with metallic zirconium



Graphite crucible coated with TaC

Methodical tests for studying of corium jet dropping flow mode




SLAVA Facility

Jet of melted stainless steel (T=2100°C)






Corium jet (T=3000°C)



**Corium mass – 60 kg
Corium content – UO₂/ Zr/ ZrO₂/SS**

Results of the fuel-coolant (water) interaction tests (FCI tests)




Results of fuel-coolant (water) interaction tests (FCI tests)




Fragmented debris after FCI



Melt discharging in the test section




Fragmented debris after FCI



Results of debris particles size distribution after FCI tests


Results of molten core concrete interaction tests (MCCI tests)



LAVA-M Facility

Corium mass - 60 kg.
Corium content - $\text{UO}_2/\text{Zr}/\text{ZrO}_2/\text{SS}$
Corium temperature - 3000°C

Simulation of residual heat release
in fuel was made by inducting
heating of corium discharged
into trap



Solidified melt in concrete trap

Description of the LAVA-B facility





Fig. 2

Description of the LAVA-B facility



BASIC TECHNICAL CHARACTERISTICS OF LAVA-B FACILITY MELT RECEIVER (MR)

• Vessel inner diameter, mm	1800
• Maximum length of inner cavity, mm	2510
• Vessel wall thickness, mm	Not less than 30
• Vessel mass (without thermal insulation), kg	~8300
• Removable lid mass (without a cart), kg	~2500
• Operating pressure, MPa:	
• – under stationary mode	4.0
• – under pulsed mode	up to 6.0
• Accessible temperature in MR cavity, °C	up to 600
• Upper flange diameter, mm	200
• Structural access door, mm	400
• Quantity of viewing windows	4
• Thickness of internal heat-insulation, mm	30
• Thermal conductivity of thermal insulation, W/m*K	0.5


LIST OF MEASURING MEANS LOCATED IN THE MR OF «LAVA-B» FACILITY

• P01	Pressure sensor	0.1–5.0 MPa
• P02	Pressure sensor	0.1–5.0 MPa
• P03	Impulse pressure sensor	0.1–5.0 MPa
• P04	Impulse pressure sensor	0.1–10.0 MPa
• T01	Thermocouple (CA type)*	273–1000 K
• T02	Thermocouple (CA type)*	273–1000 K
• T03	Thermocouple (CA type)	273–1000 K
• T04-1	Thermocouple (CA type)	273–1000 K
• T04-2	Thermocouple (CA type)	273–500 K
• T04-3	Resistance thermometer	373–500 K
• T05	Thermocouple (CA type)	273–1000 K
• T06	Thermocouple (CA type)	273–1000 K
• HF1	Heat flow sensor	up to 5 kW/m ²
• HF4	Heat flow sensor	up to 5 kW/m ²
• HF5	Heat flow sensor	up to 5 kW/m ²
• HF6	Heat flow sensor	up to 1 kW/m ²
• DP01	Differential pressure sensor	0.004 MPa
• Pyro.	Pyrometer	~3300 K
• V01.	High speed video camera	up to 100 frame/sec

*thermocouple with a shielding screen




Views of the “LAVA-B” facility melt receiver with experimental sections




- 1-Structural access door; 2-Current lead of the inductor;
- 3-Removable cover; 4-Pressure vessel; 5- Upper flange;
- 6-Viewing window; 7-Bottom welded; 8-Concrete trap;
- 9-Inductor; 10-Construction branch pipe; 11-Vapor-gas input;
- 12-Trap trolley;13-Support screw; 14-Rail; 15-Cover trolley;
- 16-Skid; 17- Rail for cover trolley; 18-Lead screw.

MELT RECEIVER WITH CONCRETE TRAP USED AT MCCI TESTS PERFORMING



- 1- Technological hatch; 2- Removable lid; 3- Power vessel
- 4- Viewing window;5- Mouth flange; 6- Plug catcher; 7- Device for water filling;
- 8- Lower head model;9- Concrete rack; 10- Steam supply manifold; 11- Trap trolley;
- 12- Support screw; 13- Trail; 14- Support frame;15- Trail of lid trolley; 16- Lid trolley;
- 17- Lead screw.

MELT RECEIVER WITH LOWER HEAD MODEL AT LHI TESTS PERFORMING




MELT RECEIVER WITH LOWER HEAD MODEL AND MELT HEATER USED AT IVR-AM TESTS PERFORMING

Experimental section - the lower head model used at **IVR-AM tests** performing


THE LOWER HEAD MODEL LOCATED IN MR



TECHNOLOGICAL BASE WITH WATER COOLING SYSTEMS SUPPLY



THE TEST SECTION ASSEMBLED WITH LOWER HEAD MODEL AND ELECTRICAL MELT HEATER



Results of molten core concrete interaction tests (MCCI tests)

MAJOR INDUCTOR HEATER PARAMETERS

Inductor coils quantity	- 6
Height between current leads, mm	- 180
Average diameter of coil turns, mm	- 450
Coil material – copper tube	- 30×5
Working current frequency, Hz	~ 2400
Inductor current value, A	~ 3580
Inductor voltage, V	~ 830
Coil current density, A/mm ²	~ 28
Active inductor power, kWt	~ 130
Duration of continuous inductor work, hour	~ 2
Flow rate of water to cool the inductor, kg/ s	- 0,3

RESULTS OF MCCI TESTS AT DIFFERENT GEOMETRY AND STRUCTURE OF CONCRETE TRAP



CONCRETE TRAP AND INDUCTION HEATER LOCATED IN MR AND PREPARED FOR CALIBRATION TESTS




TRAP DIAMETER TO DEBRIS HEIGHT RATIO IS ~1,6:1 TRAP DIAMETER TO DEBRIS HEIGHT RATIO IS ~1:1




1-D INTERACTION (SIDEWALL MADE FROM MGO) TRAP LINING WITH MORTAR (WITHOUT PEBBLES)

The views of lower head model cut after LHI tests performing using LAVA-B facility




LOWER HEAD MODEL AFTER TEST



CUTTING OF THE LOWER HEAD



SOLIDIFIED INGOT DEBRIS IN LOWER HEAD MODEL



Electrical heater for simulating of decay heat in debris at IVR-AM tests performing



THE TEST SECTION ASSEMBLED WITH LOWER HEAD MODEL AND ELECTRICAL MELT HEATER




THE LOWER HEAD MODEL WITH ELECTRICAL MELT HEATER ARE LOCATED IN MR OF LAVA-B FACILITY



COMBINED ELECTRODE

MAJOR MELT HEATER PARAMETERS

- Amount of the combined electrodes 3
- Capacity of the power supply of a direct current, kW 15×3
- Amount of sources of a direct current 3
- Voltage of the direct current source idling, V 170
- Range of the direct current change in an electrode circuit, A 5-315
- Regulation of the alternating current power supply voltage, V 8-41,6
- Maximum achievable voltage between electrodes, V 76,3
- The maximal value of an alternating current on an electrode, kA 8
- Time of processing, hour 2





"BASIC PARAMETERS" WINDOW OF THE POWER CONTROL SYSTEM

The preparation tests with electrical heater for simulating of decay heat in debris at **IVR-AM tests** performing

THE PREPARATION TESTS WITH ELECTRICAL MELT HEATER AT ALTERNATING CURRENT OPERATION



THE PREPARATION TEST WITH ELECTRICAL MELT HEATER AT DIRECT CURRENT OPERATION



Parameters and conditions of **IVR-AM** test conducting

LOWER HEAD MODELS WITH MELT AFTER EXPERIMENT IVR-1



LHM INNER SURFACE AFTER DEBRIS REMOVAL



PARAMETERS AND CONDITIONS OF **IVR-AM TEST** CONDUCTING

Lower head model (LHM)

- 500 mm in diameter
- 25 mm wall thickness

Loaded burden in electric melt furnace crucible

- PWR imitation
(78%UO₂ + 17%ZrO₂ + 5%Zr)

Discharged corium mass

- up to 50 kg

Decay heat power

- electric arc in co-axial electrodes - up to 36 kW
- direct heating using 3-phase alternating current - up to 40 kW


Time of test

- 2 hours

Cooling

- water-supply for cooling of LHM external surface - 1500 liters
- water-supply for cooling of LHM inside surface - 700 liters

APPROXIMATE SCHEME OF DEBRIS LOCATION IN LHM



Conclusion

- NNC possesses the electro thermal stand for the experimental research of the processes accompanying interaction of LWR core materials melt with the reactor pressure vessel material (LHI) and concrete (MCCI) with the maximal weight of discharged melt up to 60 kg.
- Uranium dioxide of natural enrichment comprises into corium composition, and also materials of fuel rod cladding and core constructive materials.
- Decay heat is modeled at research of the above-stated processes via the induction heating method (in MCCI experiments) via method of electric arc heating or via direct electric current through corium (in IVR-AM experiments).
- Properties of materials of the electrical melting furnace and corium at high temperature can be investigated during small-scale experiments at VCG-135stand.